





## LED SIGN MODULES

Model No.	LED type	Emitting Color	Module Pitch (mm)	Lumens & Luminosity	Voltage & Wattage	Beam Angle	Dimension of module & Application	Image
LED MODULES FOR INTERNAL ILLUMINATION OF LIGHTBOX								
M-WIDE ANGLE-BAR	Nichia 757 LED, 1.0Watt	White	150mm±5%	720 lm	24VDC 7.2Watt	175°	NICHIA led backlit strip, 50cm long for signbox whose depth is: 35~80mm. 175° wide angle with even illumination. 6LED * 1.2 W/LED (7.2Watt, 720 Lm)	
M-WIDE ANGLE-SM	Nichia 757 LED, 1.0Watt	White	150mm±5%	110~120	24VDC 1.2Watt	175°	NICHIA led backlit module, 44x35x7.5(mm), for sign boxes with depth from 35~80mm, IP65, light spreaded evenly if 15 pcs per m².	
M-WIDE ANGLE-LG	Nichia 757 LED, 1.0Watt	White	150mm±5%	100~110	24VDC 1.2Watt	160°	NICHIA LED inside, 40x35x3.5 (mm) , 24V, designed as backlights to sign boxes with depth from 120~200mm, IP65, bright enough & light spreaded evenly if 15 pcs per m².	
M-EDGE	Nichia 757 LED, 1.0Watt	White	100mm±5%	120 lm	24VDC 1.2Watt	56°*12°	NICHIA LED inside, 50x30x11 (mm) , 24V, for two-side-illuminated sign box, IP65, 35000H, Cuttable each 3 pieces	
M-RGB	Samsung led, SMD5152	RGB	100mm±5%	R=619-635 B=463-475 G=512-528	12VDC .72W	120°	SAMSUNG 3 LEDS 78mmx15mmx2mm	