



























## LED NEON FLEX SERIES

| Model No.                      | Technical Parameters  | Images  |
|--------------------------------|---|---|
| <b>NEON FLEX DOMED</b>         |   |   |
| N-DOMED-W                      | <p>LED Type: SMD 5050<br/>           Material: PVC Milky White<br/>           Working Voltage: DC24V<br/>           Rated Power/m: 12W<br/>           LED Qty/m: 60LEDs<br/>           Connection Length: &gt;20m<br/>           IP Rating: IP68<br/> <b>Min. Cutting Unit:</b><br/>           R/Y/O: 10LEDs, B/G/W:6 LEDs<br/> <b>Min. Cutting Length:</b><br/>           R/A/O: 16.67cm, B/G/W/LY:10cm<br/>           Color temperature option: 6500K/5000K/ 4500K/4000K/3000K/2700K/<br/>           Packing: 20m/reel, 10.5kg/ctn, Ctn size: 33*33*18cm</p>  |   |
| N-DOMED-R                      | Red Color, Wave Length: 620-625nm   |   |
| N-DOMED-Y                      | Lemon Yellow Color, Wave Length: 570-575nm  |   |
| N-DOMED-A                      | Amber Color, Wave Length: 590-595nm   |   |
| N-DOMED-O                      | Orange Color, Wave Length: 600-610nm  |   |
| N-DOMED-G                      | Green Color, Wave Length: 520-525nm   |   |
| N-DOMED-B                      | Blue Color, Wave Length: 465-470nm  |   |
| <b>NEON FLEX DOMED RGB</b>     |   |   |
| N-DOMED-RGB                    | <p>LED Type: <b>SMD 5050 tri-chip</b><br/>           Material: PVC -Ivory White<br/>           Working Voltage: DC24V<br/>           Rated Power/m: 12W<br/>           LED Qty/m: <b>60LEDs</b><br/>           Distance: 1.67cm<br/>           Connection Length: &gt;10m<br/>           IP Rating: IP68<br/>           Min. Cutting Unit: 10LEDs<br/>           Min. Cutting Length : 10cm</p>    |   |
| <b>NEON FLEX DOMED RGB DMX</b> |   |   |
| N-DOMED-RGB-DMX                | <p>LED Type: SMD 5050 tri-chip<br/>           Material: PVC-Ivory White<br/>           Working Voltage: DC24V<br/>           Rated Power/m: 12W<br/>           LED Qty/m: 56LEDs<br/>           LED Distance: 1.78cm<br/>           Min. Cutting Unit: 7LEDs<br/>           Min. Cutting Unit: 12.5cm<br/>           Connection Length: <b>7m power on one end, 15m on both ends</b><br/>           IP Rating: IP68<br/> <b>Singal:</b> Compatible with DMX512, and extended DMX512<br/> <b>Max pixels in one line:</b> 512 pixels if using standard</p>      |    |

| NEON FLEX FLAT          |  |   |
|-------------------------|--|---|
| N-HALO-FLAT-W           | <p>LED Type: SMD 5050<br/> Material: PVC Milky White<br/> Working Voltage: DC24V<br/> Rated Power/m: 12W<br/> LED Qty/m: 60LEDs<br/> Connection Length: &gt;20m<br/> IP Rating: IP68<br/> Min. Cutting Unit:<br/> R/A/O: 10LEDs, B/G/W/LY:6 LEDs<br/> Min. Cutting Length:<br/> R/A/O: 16.67cm, B/G/W/LY:10cm<br/> Color temperature option: 6500K/5000K/ 4500K/4000K/3000K/2700K<br/> Packing: 20m*2pcs/reel, 14kg/ctn, Ctn size: 33*33*18cm</p>  | <br>    |
| N-HALO-FLAT-R           | Red Color, Wave Length: 620-625nm  |    |
| N-HALO-FLAT-Y           | Lemon Yellow Color, Wave Length: 570-575nm   |    |
| N-HALO-FLAT-A           | Amber Color, Wave Length: 590-595nm  |    |
| N-HALO-FLAT-O           | Orange Color, Wave Length: 600-610nm   |    |
| N-HALO-FLAT-G           | Green Color, Wave Length: 520-525nm  |    |
| N-HALO-FLAT-B           | Blue Color, Wave Length: 465-470nm   |    |
| HALO NEON FLEX SIDEVIEW |  |   |
| N-SIDEVIEW-W            | <p>LED Type: SMD 5050<br/> Material: PVC-Ivory White<br/> Working Voltage: DC24V<br/> Rated Power/m: 10W<br/> LED Qty/m: <b>144LEDS</b><br/> Min. Cutting Unit: <b>12LEDS</b><br/> Min. Cutting Length: 8.33cm<br/> Connection length&gt;10m<br/> IP Rating: ip68<br/> Color temperature option:<br/> 6500K/5700K/5000K/4500K/4000K/3500K/3000K/2700K</p>      | <br> |
| N-SIDEVIEW-R            | Red Color, Wave Length: 620-625nm  |    |
| N-SIDEVIEW-Y            | Lemon Yellow Color, Wave Length: 570-575nm   |    |
| N-SIDEVIEW-A            | Amber Color, Wave Length: 590-595nm  |    |
| N-SIDEVIEW-O            | Orange Color, Wave Length: 600-610nm   |    |
| N-SIDEVIEW-G            | Green Color, Wave Length: 520-525nm  |    |
| N-SIDEVIEW-B            | Blue Color, Wave Length: 465-470nm   |    |

|                | NEON FLEX ACCESSORIES   |   |
|----------------|---|---|
| N-LEAD-RIGHT   | Mould injection connector. Cable output side: <b>Right</b><br>Cable Length: 0.6m. Mould injection end cap<br>Seamless joint connecton. Protection Rating IP68                 |    |
| N-LEAD-LEFT    | Mould injection connector. Cable output side: <b>Left</b><br>Cable Length: 0.6m. Mould injection end cap<br>Seamless joint connecton. Protection Rating IP68                  |    |
| N-LEAD-L/R     | Mould injection connector. Cable output side: <b>Left and Right</b><br>Cable Length: 0.6m. Mould injection end cap<br>Seamless joint connecton. Protection Rating IP68        |    |
| N-LEAD-L/R-M/F | Mould injection connector. Cable output side: <b>Left and Right</b><br>Cable Length: 0.3m with female and male connectors<br>Seamless joint connecton. Protection Rating IP68 |    |
| N-CHANNEL      | Aluminum Mounting Channel<br>Length: 2m<br>Holes: 2   |    |
| N-M/CLIPS      | Aluminum Mounting Clip<br>Length: 5cm<br>Holes: 2   |    |
| N-CHANNEL-02   | Aluminum Mounting Channel 02 Model<br>Length: 2m<br>Holes: 2  |    |
| N-M/CLIPS-02   | Aluminum Mounting Clip 02 Model<br>Length: 2m<br>Holes: 2   |  |