



LED SIGN MODULES

www.displaylighting.co.nz 09 427 5310



display
lighting

LED SIGN MODULES

LED Sign Modules are designed for back lighting channel letters, light boxes and general, architectural lighting purposes. Our LED Sign modules offer an impressive lumen per watt output, are available in a variety of colours and beam angles and are suitable for internal or external lighting environments. Their compact size and low voltage makes them easy to install, and economical to run, moisture-proof & fire retardant (94V0 class). Led Sign Modules are available in strands of 20/21 and are easy to install with their adhesive backings and screw holes.

All our LED Sign Modules are 100% age tested, CE-certified, RoHS compliant and C/UL-listed (file number: E468389), power saving, moisture-proof & fire retardant (94V0 class)

BACKLIT I MODULE

Designed to evenly illuminate sign boxes, can connect up to 25 modules.



IP67

CODE	WATTAGE	VOLTAGE	LUMENS	BEAM ANGLE
M-BACKLIT-ONE	1	12V	90lm	160°

RGB BACKLIGHT MODULE

Suitable for backlighting sign boxes, letters and halo backlighting where colour change or a particular colour is required.



IP65

CODE	WATTAGE	VOLTAGE	LUMENS	BEAM ANGLE
M-RGB	.72	12V	200lm	120°

BACKLIT II MODULE

Designed to illuminate sign boxes and channel letters, can connect up to 25 modules.



IP67

CODE	WATTAGE	VOLTAGE	LUMENS	BEAM ANGLE
M-BACKLIT-TWO	1.2	12V	76lm	160°

SIDE MODULE

Designed to evenly illuminate two-sided signs, can connect up to 13 modules.



IP67

CODE	WATTAGE	VOLTAGE	LUMENS	BEAM ANGLE
M-SIDE	2	12V	175lm	60° & 10°

BACKLIT III MODULE

Designed to illuminate sign boxes and channel letters, can connect up to 25 modules.



IP67

CODE	WATTAGE	VOLTAGE	LUMENS	BEAM ANGLE
M-BACKLIT-THREE	1.3	12V	130lm	160°

BACKLIT IIII MODULE

Designed to evenly illuminate sign boxes, can connect up to 20 modules.



IP67

CODE	WATTAGE	VOLTAGE	LUMENS	BEAM ANGLE
M-BACKLIT-FOUR	2	12V	150lm	160°

* Other options available, please contact the team to discuss your requirements.

